



Walter G. **LEGGE** Co., Inc.
444 Central Ave., Peekskill, NY 10566
tel # 800-345-3443 fax 800-332-2636
email address: info@leggesystems.com
website: www.leggesystems.com

LEGSHIELD S300

Impregnator Seal & Water Repellent
For Interior and Exterior use

LEGSHIELD S300 is a water based, silicone seal and water repellent designed to form an impervious penetrating seal. It is designed to chemically react to the minerals below the surface-forming an impervious seal that repels water, oil, and dirt. **LEGSHIELD S300** has exceptional durability, water and stain resistance, with no change in appearance (on unpolished, unglazed surfaces). Only one application is required - DO NOT RECOAT. May be used on manufactured and natural stones (such as limestone, sandstone and ceramics), bricks, concrete and decorative tile. **LEGSHIELD S300** is colorless, non-yellowing with low VOC.

APPLICATION INSTRUCTIONS

The proper application of **LEGSHIELD S300** is critical in obtaining optimum results. **LEGSHIELD S300** should only be applied to clean, unsealed and slightly damp surfaces. Apply an even coat to the entire surface. DO NOT LEAVE PUDDLES. The main function of a penetrating seal is to form a breathable barrier below the surface, without affecting the original appearance of the material. During application any excess seal remaining on the surface must be removed immediately. This can be accomplished with either a squeegee or a lint free cloth. If a white precipitate should form due to excessive amount, rundown or overlapping, let **LEGSHIELD S300** cure for 72 hours and scrub thoroughly with a solution of 6 ounces of **LEGCLEAN** per gallon of water.